


Product	Power Supply, Open frame Building-in Type
Applicant	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Manufacturer	Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon, Hong Kong
Factory	(2) See page 2
Ratings	2.3A, 100-250V, 50/60/440Hz or 1.5A 120V-300V DC
Trade mark	
Model / Type Ref.	LPS62
Principal characteristics	Cl. I, DC-output: 16A +5V. Maximum output power: 60W convection cooling, 80W with 30CFM forced air.
A sample of the product was tested and found to be in conformity with	OFF                      EN 60950-1:2006;A11;A1;A12;A2
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(3) See page 2

Date of issue 07-01-2016



Nastaran Vadoodi  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532

### Additional model(s)

Product Power Supply, Open frame Building-in Type  
Pos. No 1  
Model / Type Ref. LPS64  
Trade mark (if different from page 1)  
Rating 2.3A 100-250V 50/60/440Hz or 1.5A 120V-300V DC  
Principal characteristics Cl. I, DC-output: 5.3A +15V. Maximum output power: 60W convection cooling, 80W with 30CFM forced air.

Product Power Supply, Open frame Building-in Type  
Pos. No 2  
Model / Type Ref. LPS65  
Trade mark (if different from page 1)  
Rating 2.3A 100-250V 50/60/440Hz or 1.5A 120V-300V DC  
Principal characteristics Cl. I, DC-output: 3.3A +24V. Maximum output power: 60W convection cooling, 80W with 30CFM forced air.

Product Power Supply, Open frame Building-in Type  
Pos. No 3  
Model / Type Ref. LPS63  
Trade mark (if different from page 1)  
Rating 2.3A 100-250V 50/60/440Hz or 1.5A 120V-300V DC  
Principal characteristics Cl. I, DC-output: 6.7A +12V. Maximum output power: 60W convection cooling, 80W with 30CFM forced air.

### Factories

Astec Power Philippines Inc.  
Main Avenue Corner Road "J" Cavite Export Processing  
Zone Rosario, Cavite, 4106  
Philippines

Astec Power Philippines Inc.  
104 Laguna Blvd., Laguna Technopark, Sta. Rosa  
Laguna, 4026  
Philippines

Date of issue 07-01-2016



Nastaran Vadoodi  
Certification Department

**Nemko AS**  
Gaustadalléen 30, P.O. Box 73 Blindern, 0314 Oslo, Norway  
TEL +47 22 96 03 30 FAX +47 22 96 05 50 EMAIL info@nemko.com  
ENTERPRISE NUMBER NO974404532